



VKT-Tuotanto

Myyntipäivystäjä p. 0500-738122

puh. 09-2970201 fax 09-2970093

www.vkt-tuotanto.fi

myynti@vkt-tuotanto.fi

Nyåkerintie 37, 02420 Jorvas



CE-M -hyväksyntä



Ulkoinen kalibrointi



Kappalelaskenta



GLP-yhteensopivuus



Toleranssipunnitus



Eläinpunnitusohjelma



RS 232 -liitäntä



Verkkovirtakäyttö

Lisätilauksesta



Akkukäyttö



Kalibrointitodistus

KERN BFS

Tasovaaka joka voidaan varustaa päälleajorampilla tai upottaa lattiaan.

- 5 mallia. Punnitus 600 kg / 200 g - 3000 kg / 1 kg.
- CE-M -hyväksytty
- Tason mitat: 1000 x 1000 mm, korkeus 80 mm (BFS-S).
- Tason mitat: 1500 x 1250 mm, korkeus 80 mm (BFS).
- Päälleajorampin mitat: 1000 x 840 mm, lisävaruste (BFS-S).
- Päälleajorampin mitat: 1250 x 840 mm, lisävaruste (BFS).
- LCD-näyttö, numerokoko 52 mm.
- Verkkovirtakäyttö. Akut lisävarusteena.
- Punnitusanturit vesitiiviit, luokka IP67.
- Käyttölämpötila -10 C / 40 C
- Materiaali polttomaalattu teräs. Pinta luistoa estävästi käsiteltyä kynnelleppyä.
- **Toiminnot:** Punnitus, tarkistus-punnitus, eläinpunnitus-ohjelma ja painonpito näytössä. Painotiedon summaus.
- **Lisätarvikkeet:** Näytön lattiajalusta, päälleajoramppi ja lattiaanupotuskehys. Lattiaankiinnityssarja..Lämpöpaperi- ja tarraetikettitulostimet. Akkukäyttö.
- Saatavissa myös kalibrointitodistus.
- Katso mallit ja kuvat alla olevasta valmistajan esitteestä.

KERN BFS Robust floor scale with piece-counting function



CAL EXT **Adjusting program (CAL):** For quick setting of the balance's accuracy. External adjusting weight required.

PCS **Piece counting:** Reference quantities selectable. Display can be switched from piece to weight.

GLP **GLP/ISO record keeping** of weighing data with date, time and ident.-no. Only with printers from KERN.

PC IT-Net **Data interface:** The type of interface is shown by the pictogram. For a definition, see glossary.

TOL **Weighing with tolerance range:** Upper and lower limiting can be programmed individually, e.g. dosing / sorting.

230V **Mains adapter:** 230 V/50Hz in standard version for Germany. On request GB, AUS or USA version.

Option (additional price)

AKU **Rechargeable battery pack:** rechargeable set.

Delivery
2 days

3
Years warranty

Strain gauge

OPTION DKD
Certificate +3 days

Large backlit LCD displays digit height 13/16 mm

Benchtop stand incl. wall mount for display device as standard

Comfortable adjustment of the weighing bridge from above


- 1 Weight display
- 2 Reference weight
- 3 Total count

Easy access to the junction box from the top

- STANDARD**
- CAL EXT
 - PCS
 - GLP
 - PC RS 232
 - TOL
 - 230V
- OPTION**
- AKU



Column to elevate the display device, column height approx. 750 mm, **KERN BFS-A07**



Stable pit frame to install the weighing bridge so you can drive straight on. For weighing plate size [A] WxDxH 1090x1090x86 mm, **KERN BFS-A03** [B] WxDxH 1590x1340x86 mm, **KERN BFS-A04**

PCS **Precise counting** The manual optimisation of reference weight improves the average value of the parts weight in levels

TOL **Weighing with tolerance range** (checkweighing) Input of an upper/lower limit value. A visual and acoustic signal assists with portion division, dispensing or grading to counting mode

Ascending ramp for weighing plate size [A] WxD 1000x840 mm, **KERN BFS-A01** [B] WxD 1250x840 mm, **KERN BFS-A02**

Totalizing of counting operations

Pair of base plates to fix the weighing bridge to the floor, not standard **KERN BFS-A06**

AKU **Rechargeable battery pack** internal, operating time approx. 30 h, charging time approx. 12 h, **KERN KFS-A01**

Weighing bridge anti-slip corrugated steel plate, lacquered, overall height 80 mm

Standard printer **KERN YKB-01N**

Label printer **KERN YKL-01**

1 Statistics printer **KERN YKT-01**

For all printers see page 109

Technical data:

Display device WxDxH 250x160x65 mm

Permissible ambient temperature 0 ...+40 °C

Model	Weighing range Max kg	Read-out d g	Verific. value e g	Min. piece weight at piece count. g/piece	Net weight approx. kg	Cable length approx. m	Weighing plate	OPTION DKD Certificate KERN
KERN								
BFS 600K200S	600	200	± 400	200	85	5	A	963-130
BFS 600K200	600	200	± 400	200	204	5	B	963-130
BFS 1.5T0.5S	1500	500	± 1000	500	85	5	A	963-130
BFS 1.5T0.5	1500	500	± 1000	500	204	5	B	963-130
BFS 3T1	3000	1000	± 2000	1000	204	5	B	963-132

Order Hotline: Go to back page of catalogue

63

KERN – ihr DKD-Kalibrierpartner

issues DKD calibration certificates for balances and test weights in its own accredited laboratories. It is internationally valid.

KERN is a manufacturer of test weights in the international classes of accuracy **E1, E2, F1, F2, M1, M2, M3, from 1 mg up to 2000 kg**
DKD = German Calibration Service



Your KERN specialist dealer