



VKT-Tuotanto

Myyntipäivystäjä p. 0500-738122

puh. 09-2970201 fax 09-2970093

www.vkt-tuotanto.fi

myynti@vkt-tuotanto.fi

Nyåkerintie 37, 02420 Jorvas




CE-M -hyväksyntä



Akkukäyttö




Ulkoinen kalibrointi



Taaraus



Anturien tiiviysluokka



Näytön tiiviysluokka



RST-rakenne

Dini Argeo TPWLKI

- Punnitus 2000 kg, tarkkuus 0,2 / 0,5 / 1 kg.
- CE-M kaksialuehyväksytyt tarkkuudella 0,5 / 1 kg
- Rakenne RST-terästä, nostopumppu myös RST-teräksinen.
- Punnitusanturit vesitiiviit, luokka IP-68.
- Näyttölaite roiskevesitiivis, luokka IP-65
- Akkukäyttöinen. Toiminta-aika n. 80 tuntia / lataus.
- LCD-näyttö, numerokoko 25 mm.
- Lisätilauksesta lämpöpaperitulostin jolla painotiedot saa luotettavasti talteen.
- Automaattinen virrankatkaisu.
- Käyttölämpötila -10 - + 40C.
- **Toiminnot:** Nollaus, automaattinen taaraus, aseteltava taara. Kymmenkertainen näyttötarkkuus. Netto/brutto. Punnitusten summaus. Kaavapunnitus. Tarkistuspunnitus. Prosenttipunnitus. Kappalelaskenta . Painon pito näytössä ja suurimman painon pito.
- **Lisätilauksena:** Lämpöpaperiprintteri, radiomodeemi, WI-FI, alibimuisti (120 000 punnitusta), kellonaika/päiväys, 2 sisäämenoa + 2 ulosottoa (brutto-, nettopaino).
- Katso kuva alla olevasta valmistajan esitteestä.

TPWLKI SERIES STAINLESS STEEL PALLET TRUCK SCALE

Stainless steel pallet truck scales with built-in multirange electronic weighing, easy to use. Weight detection with four IP68 stainless steel load cells. Sturdy structure suitable for harsh work conditions. Available also CE-M APPROVED.

MAIN FEATURES

- Maximum lifting capacity: 2000 kg.
- Accuracy +/- 0.1% of the maximum capacity.
- Fork dimensions 1180 x 550 x 80 mm. Weighs about 135 kg.
- **Bearing structure entirely in extra thick STAINLESS steel.**
- **Lifting pump in STAINLESS steel.**
- Steering wheels and double loading rollers in nylon.
- 4 IP68 stainless steel shear beam load cells.
- IP65 stainless steel weight indicator, easy to clean and resistant to harsh and corrosive environments; large 25mm backlit LCD display, clearly visible also in poor lighting conditions, and waterproof keypad, with 17 numerical/functional keys.
- Calibration and Set-Up from keyboard or from PC.
- Power supply through built-in rechargeable battery.
- 80-hour approximate operating time or one month with the typical non continuous use, thanks to its auto switch-off function.
- Programmable auto power saving function.
- Low battery warning.
- Equipped with 230Vac 50 Hz battery charger (recharging time is about 8 hours).
- Bi-directional RS232/C port for connection to printer.
- Bi-directional RS232/C port for PC, radio modem, or portable terminal.
- IR input for managing the remote control

MAIN FUNCTIONS

- **High Resolution Weighing x 10**
- **Net/Gross or lb/kg conversion**
- **Accumulation**
- **Formula weighing**
- **+/- Checkweighing**
- **Percentage weighing**
- **Counting** (Max. resolution of 1.500.000 divisions)
- **In/Out weighing**

OPTIONS ONLY AVAILABLE AT TIME OF ORDER

- Thermal printer / Modem radio option box
- WI-FI interface
- Alibi memory with time-date
- Time-Date
- Versions with special capacities and/or divisions or high resolution (ask for price estimate)

KEYBOARD AND PRINT FUNCTIONS

- **KEYBOARD:** Zeroing, automatic tare, print and/or data transmission command, activation of selected function, presettable tare, ID1 code, ID2 code, 10 recallable tare values.
- **PRINTOUT:** configurable layout with:
4 header rows, net weight, gross weight, tare weight or weight totalized and total weigh, time/date, ticket number, weigh number.



SOFTWARE SCALEMONITOR



Scalemonitor is a simple and economical solution for receiving the weight data from PC to one or more scales, and making them suitable and sorting in the most common office format



discover
SCALEMONITOR

Available versions

Code	Max Capacity kg	Division kg	CE-M Division kg	HR Division kg
TPWLKI	500 / 1000 / 2000	0,2 / 0,5 / 1	--	0,1
TPWLKIM	1000 / 2000	--	0,5/1	--

Options only available at time of order

Code	Description
EHR	High resolution model for internal factory use.
TPRXTP	Thermal printer for mounting on the pallet truck column, with stainless steel case and ABS door for protection from sprays and dust. IP65 protection.
DFCLK	Real time clock for printing/displaying of the date and time.
ALMEM	Alibi memory (fiscal memory, max 120.000 weighs) for approved transmission of the weight to PC/PLC. Real time clock integrated for print of the date/time.
WIFIT	WI-FI interface for wireless connection (through access point) to the company computer system.

Accessories

Code	Description
UKPLUG	Power adapter from Schuko to BS1363.
TECMAN	Printed technical manual (free, if downloaded from the web). NET PRICE.
UMAN	Printed user manual (free, if downloaded from the web and available in the CD, fitted with the product). NET PRICE.