



VKT-Tuotanto

Myyntipäivystäjä p. 0500-738122

puh. 09-2970201 fax 09-2970093

www.vkt-tuotanto.fi

myynti@vkt-tuotanto.fi

Nyåkerintie 37, 02420 Jorvas



IP 67

Roiskevesitiivis



INOX

Ruostumatonta terästä



BATT

Paristokäyttö



CAL EXT

Ulkoinen kalibrointi



UNIT

Painoyksikön valinta



TARE

Taaraus



DMS

Kern FFN

- 3 mallia. Punnitus 3 kg / 0,5 g -15 kg / 2 g.
 - Roiskevesitiivis, luokka IP-67.
 - Tason koko 230 X 190 mm.
 - LCD näyttö, numerokoko 25 mm.
 - Paristokäyttöinen. 4 X 1,5 V D.
 - Automaattinen sammutus.
- Säästö toiminnolla paristojen kesto N. 600 tuntia.*
- Katso sopiva malli alla olevasta valmistajan esitteestä.



KERN FFN Robust bench scale with large weighing range, protected by stainless steel and IP67



STANDARD



Adjusting program (CAL): For quick setting of the balance's accuracy. External adjusting weight required.



Weighing units: can be switched to e.g. non-metric units at the touch of a key. See balance model.



Spray and dust protection: The type of protection is shown by the pictogram. For a definition see the glossary.



Stainless steel: the balance is protected against corrosion.



Battery operation: The battery type is specified for each device.



Tare: put back displayed value to „0“ during weighing process, e.g. to add or remove weighing material from a container.

Carrying grips ▶ on the underside of the scale for easy transportation



Housing made of stainless steel, so it is rustproof and easy to clean

Level indicator and foot screws to level the balance precisely, fitted as standard, to give the most accurate weighing results



Ready for use Batteries size D (4 x 1.5 V) included. Operating time approx. 12 months. AUTO-OFF function to preserve battery life, can be switched off

Large LCD Display digit height 25 mm



Ideal for the robust industry



Ideal for the food industry



IP67 protection high level of protection against dust and water. Ideal for harsh environmental conditions. Designed for temporary use in wet areas

Technical Data:

Overall dimensions WxDxH 230x300x130 mm
Net weight approx. 3,2 kg
Permissible ambient temperature -10 ... +40 °C
UNITS Further weighing units: see the internet
 No mains adapter available

Model	Weighing range Max kg	Read-out d g	Reproducibility g	Linearity g	Weighing plate	OPTION DKD Certificate KERN
FFN 3K0.5IP	3	0,5	0,5	± 1	230 x 190	963-127
FFN 6K1IP	6	1	1	± 2	230 x 190	963-128
FFN 15K2IP	15	2	2	± 4	230 x 190	963-128

92

Order Hotline: Go to back page of catalogue

KERN - Your DKD-Calibration Partner

issues DKD calibration certificates for balances and test weights in its own accredited laboratories. It is internationally valid.

KERN is a manufacturer of test weights in the international classes of accuracy E1, E2, F1, F2, M1, M2, M3, from 1 mg up to 2000 kg
DKD = German Calibration Service



Your KERN specialist dealer