



Myyntipäivystäjä p. 0500-738122

puh. 09-2970201 fax 09-2970093

www.vkt-tuotanto.fi

myynti@vkt-tuotanto.fi

Nyåkerintie 37, 02420 Jorvas



Ulkoinen kalibrointi



Kappalelaskentaohjelma



Prosenttipunnitus



Reseptipunnitus



GLP-yhteensopivuus



RS232 -liitäntä



Painoyksikön valinta



Eläinpunnitusohjelma



Paristokäyttö



Verkkovirtakäyttö

Lisätilauksesta



Ladattavat akut



Kalibrointitodistus



Tulostin, 4 eri mallia

KERN 440

- 11 mallia. Punnitus 60 g / 0,001 g -6 kg / 0,1 g.
- Tason halkaisija 81 mm, 105 mm tai suorakaide 130 x 130 mm tai 150 x 170 mm.
- LCD-näyttö, numerokoko 15 mm.
- Verkkovirta- ja paristokäyttö. Akut lisävaruste.
- Käyttölämpötila +5C - +35C.
- RS232- liitäntä tulostimeen tai tietojärjestelmiin.
- **Toiminnot:** punnitus, kappalelaskenta, netto /brutto -punnitus, prosenttipunnitus ja eri painoyksiköt. Punnituksen tunnistus. Vaa'an alapuolinen ripustuspunnitus.
- **Lisätilauksena:** Ladattavat akut, lisänäyttö, 4 mallia tulostimia, lämpöpaperille tai tarraetiketille.
- Katso mallit ja kuvat alla olevasta valmistajan esitteestä.



KERN 440 The bestseller in basic laboratory balances



* while stocks last



Battery operation possible
Block battery (9V) not included. AUTO-OFF function after 3 min without a change of load to preserve the battery, can be switched off



Weighing plate A
ring-shaped draft shield standard,
Ø 90 mm, height 40 mm

Backlit LCD display
digit height 15 mm

Rechargeable battery pack
internal, operating time approx. 20 h, charging time approx. 10 h, KERN FCB-A01

Protective working cover
over keyboard and housing, standard. Can be reordered

For weighing plate sizes
A KERN 440-210-002
B KERN 440-330-002
C KERN 440-450-002
D KERN 440-530-002



STANDARD



only with printer 1



Data transfer
e.g. to a printer or PC

Technical Data:

Overall dimensions
WxDxH 165x230x80 mm
Net weight approx. 1,3 kg

Permissible ambient temperature +5 ... +35 °C

UNITS Further weighing units: see the internet

Adjusting program (CAL):
For quick setting of the balance's accuracy. External adjusting weight required.

Piece counting: Reference quantities selectable. Display can be switched from piece to weight.

Data interface: The type of interface is shown by the pictogram. For a definition, see glossary.

Net-total weighing: weight of tare cup and weight of components memorized in two separate stores.

Percentage determination: Displays the deviation from the reference weight (100%) in % instead of grams.

GLP/ISO record keeping of weighing data with date, time and ident.-no. Only with printers from KERN.

Weighing units: can be switched to e.g. non-metric units at the touch of a key. See balance model.

Animal weighing program: strong vibrations are filtered out.

Suspended weighing: load support with hook on the underside of the balance.

Battery operation: The battery type is specified for each device.

Mains adapter: 230 V/50Hz in standard version for Germany. On request GB, AUS or USA version.

Option (additional price)

Rechargeable battery pack: rechargeable set.

Model	Weighing range Max g	Read-out d g	Repro-ducibility g	Linearity g	Weighing plate	OPTION	
						Certificate KERN	DKD
KERN 440-21N*	40	0,001	0,001	± 0,003	A	963-127	
440-21A	60	0,001	0,001	± 0,003	A	963-127	
440-33N	200	0,01	0,01	± 0,02	B	963-127	
440-35N	400	0,01	0,01	± 0,03	B	963-127	
440-35A	600	0,01	0,01	± 0,03	B	963-127	
440-43N	400	0,1	0,1	± 0,2	C	963-127	
440-45N	1000	0,1	0,1	± 0,2	C	963-127	
440-47N	2000	0,1	0,1	± 0,2	C	963-127	
440-49N	4000	0,1	0,1	± 0,3	D	963-127	
440-49A	6000	0,1	0,1	± 0,3	D	963-128	
440-55N*	6000	0,2	0,2	± 0,6	D	963-128	
440-51N	4000	1	1	± 2	D	963-127	
440-53N	6000	1	1	± 2	D	963-128	

Order Hotline: Go to back page of catalogue

23

KERN - Your DKD-Calibration Partner

issues DKD calibration certificates for balances and test weights in its own accredited laboratories. It is internationally valid.

KERN is a manufacturer of test weights in the international classes of accuracy E1, E2, F1, F2, M1, M2, M3, from 1 mg up to 2000 kg
DKD = German Calibration Service



Your KERN specialist dealer