



Myyntipäivystäjä p. 0500-738122

puh. 09-2970201 fax 09-2970093

www.vkt-tuotanto.fi

myynti@vkt-tuotanto.fi

Nyåkerintie 37, 02420 Jorvas



CE-M III -hyväksyntä



PCS Kappalelaskenta



Prosenttipunnitus



TOL Toleranssipunnitus



RECIPE Kaavapunnitus

Lisätilauksesta

Kalibrointitodistus

Dini Argeo LTF 10 Professional

- Punnitseva trukkipiikkisarja. Sopii DIN 15173 - FEM IIA tai IIIA -haarukkakelkkaan, II B -kelkka lisävarusteena.
- 4 mallia. Punnitus 500 kg / 0,5 kg - 5000kg / 5 kg.
- **CE-M III** -luokan hyväksyntä (ARM-mallit).
- Helppo ja nopea asentaa.
- 2 näyttölaitetta, trukkipiikissä näyttö jossa radiolähetin joka siirtää tiedon hytissä olevaan näyttölaitteeseen.
- Vesitiiviit anturit IP-68.
- Tarkkuus +/-0,1 % kapasiteetista.
- Turvallinen ylikuorma 300 % kapasiteetista.
- Sallittu kulmavirhe +/- 2°.
- LCD-näyttö, numerokoko 25 mm. Varustettu taustavalolla.
- Akkukäyttö. Toiminta-aika 40 tuntia / lataus.
- **Toiminnot:** Nollaus, automaattinen taaraus, aseteltava taara. Kymmenkertainen näyttötarkkuus. Netto/brutto. Punnitusten summaus. Kaavapunnitus. Tarkistuspunnitus. Prosenttipunnitus. Kappalelaskenta . Painon pito näytössä ja suurimman painon pito.
- **Lisätilauksena:** Lämpöpaperiprintteri, radiomodeemi, WI-FI, alibimuisti (120 000 punnitusta), kellonaika/päiväys, 2 sisäämenoa + 2 ulosottoa (brutto-, nettopaino).
- Katso mallit ja kuvat alla olevasta valmistajan esitteestä.

LTF10 "PROFESSIONAL" SERIES WEIGHING KIT FOR LIFT TRUCK FORKS



LTF10: pair of weighing forks.
Indicator for mounting in the cabin, with optional printer.

Pair of forks with an integrated weighing system, for lift trucks; easy to use, sturdy, and reliable. The indicator installable in the cabin eases the weighing operations, and can be fitted with a wide range of accessories. Functions through rechargeable battery or through direct powering from the lift truck. Compatible with any lift truck having a DIN 15173 - FEM fork holder plate, of the IIA or IIIA class (IIB optional). Available CE-M approved.

MAIN FEATURES

- Weight indicator **in cabin** with 17-key numerical/functional waterproof keypad, LCD backlit display with 6 high contrast 25-mm digits and easy to clean **Waterproof IP65 ABS** case resistant to harsh and corrosive environments. Integrated radio module, for communication with the weighing forks.
- Second weight indicator, **attached to the forks**, with 5-key numerical/functional waterproof keypad, LCD backlit display with 6 high contrast 25-mm digits protected in thick steel case. Integrated radio module, for communication with the indicator in cabin.
- Structure of the forks in painted steel.
- Each fork weighs 75 kg (LTF25) and 90 kg (LTF50).
- Functions with 4 shear-beam IP68 load cells
- Accuracy: +/- 0.1% of the capacity
- Max. allowable overload: 300% of the nominal capacity.
- Max. horizontal inclination (flexibility): +/- 2° with the same precision features.
- Digital calibration and set-up through keyboard or PC with DINITOOLS.
- Forks power supply through rechargeable battery, 40-hour approximate operating time
- Indicator in cabin power supply through rechargeable battery (40-hour approximate operating time) or directly from the lift truck through optional power adapter.
- Programmable auto power saving function.
- Equipped with battery charger.

SELECTABLE FUNCTIONS

- **High Resolution Weighing x 10**
- **Net/Gross or lb/kg conversion**
- **Weighs totalisation**
- **Formulation**
- **+/- Check**
- **Percentage weighing**
- **Alibi memory, for weight approved transmission** (optional)
- **Counting**
- **Input/Output**
- **Hold and Peak**

KEYBOARD FUNCTIONS AND PRINTOUT

- **KEYBOARD:** clearing, semi automatic tare, presettable tare, print and/or data transmission, selectable function command, on/off.
- **PRINTOUT:** customisable print layout.

OPTIONS ONLY AVAILABLE AT TIME OF ORDER

- Thermal printer option box.
- Alibi memory with time/date.
- Time/Date.
- 2 inputs + 2 outputs configurable on gross or net weight.

Available versions

Code	Plate	Max Capacity kg	Division kg
LTF1025AR	FEM2A	500 / 1000 / 2500	0,5 / 1 / 2
LTF1025ARM M	FEM2A	2500	2
LTF1050AR	FEM3A	5000	5
LTF1050ARM M	FEM3A	5000	5

Options only available at time of order

Code	Description
LTFBK	Additional extractable battery for indicator attached to the forks LTF series, for using the scale 24/7.
OBTPRP	Thermal printer for mounting attached to weight indicator, with ABS case, connection cable, power supply from weight indicator.
OBMDDP	Thermal printer and memory data printer for mounting attached to weight indicator, with ABS case, connection cable, memory card, power supply from weight indicator.
OBMDC	Memory Data Printer for mounting attached to weight indicator, with ABS case, connection cable, memory card,

DFCLK	power supply from weight indicator.
DFIO	Real time clock for printing/displaying of the date and time.
DFIO	Input/output interface with 2 optoisolated digital inputs and 2 Photomosfet outputs for management setpoints with programmable weight threeshold (not combinable with ALMEM alibi memory option).
ALMEM	Alibi memory (fiscal memory, max 120.000 weighs) for approved transmission of the weight to PC/PLC. Real time clock integrated for print of the date/time.

Accessories

Code	Description
AL7212	Adjusted power adapter for direct power supply of the scale from the lift truck. Min. 36 Vdc - Max 72 Vdc IN directly from the lift truck / 12 Vdc 5A OUT (60W), for powering the weight indicator.
UKPLUG	Power adapter from Schuko to BS1363.
TECMAN	Printed technical manual (free, if downloaded from the web). NET PRICE.
UMAN	Printed user manual (free, if dowloaded from the web and available in the CD, fitted with the product). NET PRICE.