

VKT-Tuotanto

Nyåkerintie 37, 02420 Jorvas

puh. 09-2970201, myyntipäivystäjä 0500-738122

myynti@vkt-tuotanto.fi

www.vkt-tuotanto.fi



WALL-E" SERIES BENCH AND FLOOR SCALES



Bench and floor scales, with column, characterized by multifunction weight indicator, hard and sturdy structure and stainless steel loading surface. Easy to use and versatile, guaranteeing precision and reliability. Particularly suitable for industrial and commercial use. Available also in CE-M approved version according to OIML R-76 / EN 45501 standards.

TECHNICAL FEATURES

- Weight indicator with ABS case, 25mm backlit LCD display with 6 high contrast digits and icons for showing the active functions. 5-key functional waterproof keypad.
- Functioning with an aluminium load cell, 3000d approved with IP65 protection degree.
- Steel tubular structure, oven-fire painted blue, with adjustable resting feet and level.
- Stainless steel loading surface, size: see the table.
- Fitted with fixing bracket with adjustable inclination and support column, height:
 - 350 mm in the "T" models;
 - 500 mm in the "Q" models;

- 700 mm in the "X" and "E" models.
- Digital calibration and Set-Up from keypad or from PC through DINITOOLS.
- Power supply: 4 AA batteries or 230Vac power supplier.

SELECTABLE FUNCTIONS

- **x 10 high resolution visualisation**
- **Net/Gross or lb/kg conversion**
- **Weights totalisation**
- **Formulation**
- **+/- Check**
- **Percentage weigh**
- **Alibi, for approved weight transmission (optional)**
- **Counting**

I/O SECTION

- RS232/RS485 port for connection to PC, PLC or repeater.
- RS232 port configurable for connection to printer.
- IR input for managing the remote control.

Lisäominaisuudet, mainittava tilatessa

- CE-M approval (OIML R-76 / EN 45501).
- Real time clock.
- Alibi Memory.
- Infrared remote control.

- USB interface.

Lataukset Dini Argeo sivuilta

- [CE_CERTIFICATE_SCALES_150318.pdf](#)
- [DFW_03.18.15.07_EN_T.pdf](#)
- [DFW_03_08.10_RU_U.pdf](#)
- [DFW_03_09.12_ES_U.pdf](#)
- [DFW_03_12.01_CN_U.pdf](#)
- [DFW_03_12.10_EN_U.pdf](#)
- [DFW_03_12.10_RO_U.pdf](#)
- [DFW_03_14.11_DE_U.pdf](#)
- [DFW_03_14.11_EN_U.pdf](#)
- [DFW_03_14.11_FR_U.pdf](#)
- [DFW_03_14.11_IT_U.pdf](#)
- [DiniTools_4.19.00.zip](#)
- [PB_13.10_EN_DE_FR_IT.pdf](#)
- [Printout_examples_DFW.pdf](#)
- [Setup_WeiMonitor_1.5.7.zip](#)
- [Last Firmware Revision News](#)

Mallisto

Code	l x w x h (mm)	Max (kg)	d (g)	M (g)*
WET6	300x300x130	6	2	2
WET15	300x300x130	15	5	5
WET30	300x300x130	30	10	10
WEQ30	400x400x140	30	10	10
WEQ60	400x400x140	60	20	20
WEQ150	400x400x140	150	50	50
WEX60	600x600x150	60	20	20
WEX150	600x600x150	150	50	50
WEX300	600x600x150	300	100	100
WEE300	800x800x165	300	100	100
WEE600	800X800X165	600	200	200

(*) These divisions are obtainable only with the relative options

Calibration service (ACCREDIA/DAKKS) only at time of order

Code Description



CT4 ISO 17025 calibration certificate from 6 to 60 kg. For precision and industrial scales, crane scales.



CT5 ISO 17025 calibration certificate from 61 to 300 kg. For precision and industrial scales, crane scales.



CT6 ISO 17025 calibration certificate from 301 to 1500 kg. For precision and industrial scales, crane scales.

Legal for trade approval

Code Description



ECEM CE-M Single platform legal for trade approval.

Storing the weighs (only at time of order)

Code Description



SWM WeiMonitor PC program for monitoring and recording weighs in real time, from one or more scales.

Date&Time option

Code Description



DFCLK (S1) Real time clock for printing/displaying of the date and time.

Communication Interfaces

Code Description



ALMEM (S1) Alibi memory (fiscal memory, max 120.000 weighs) for approved transmission of the weight to PC/PLC or data recording on MMC/USB. Real time clock integrated for print of the date/time.

Connection cables

Code Description



RSCBRJ (S1) RS232/C serial cable - DB9/RJ11 - l=1,5m.



RSCBRJ10M (S1) RS232/C serial cable - DB9/RJ11 - l=10m.



RSCBUSB-1 (S1) USB PC/RS232 converter cable, l=1,5m. USB/RJ11 connector.

Remote control

Code Description



DFTL12-1 (S1) 19-keys remote control and infrared receiver kit (max 8m).

Columns, supports brackets, visors

Code Description



PBSTF Stainless steel fixing bracket for mounting the DFWL indicator.