

Price computing scale KERN RXB



Entry level model for your retail business, with EC type approval [M]

Features

- **1 Elevated display** backlit, revolving on column, height of stand approx. 540 mm, only RXB-HM, must be ordered at purchase
- **2 Second display** on the rear of the balance (only with models without the elevated display)
- **Three displays** for weight (verifiable), unit price, total price
- **Unit price can be switched** from €/kg to €/100 g
- **FIX key:** Unit price can be stored for further weighings of the same article
- **Energy management:** Backlight turns off after 5 sec, can be switched off

- **Soil-resistant construction** with water channels at the edge of the housing and sealing rings over the upper housing inlets

Technical data

- Large backlit LCD displays, digit height 18 mm
- Dimensions of weighing plate, stainless steel WxD 300x225 mm
- Overall dimensions WxDxH 300x330x110 mm
- Rechargeable battery pack internal, standard, operating time approx. 200 h, charging time approx. 8 h, Charge condition indicator using three-colour LED
- Net weight approx. 4,4 kg

Application examples:

- retail hops
- market places
- farms hops
- pick your own fruit and vegetable sales

Note: In commercial trade, official verification duties exist

- Permissible ambient temperature -10 °C / 40 °C

Accessories

- **Protective working cover** over keyboard and housing standard, can be reordered, KERN CXB-A01
- **Tare pan made from stainless steel**, ideal for weighing loose fruit and vegetables, WxDxH 370x240x20 mm, KERN RFS-A02

STANDARD



OPTION

































FACTORY



Model	Weighing range [Max] kg	Read-out [d] g	Verific. value [e] g	Minimum load [Min] g	Options				
					Verification		DKD Calibr. Certificate		
					M	KERN	DKD	KERN	
RXB 3K1M	3	1	1	20	965-227		963-127		
RXB 6K2M	6	2	2	40	965-228		963-128		
RXB 15K5M	15	5	5	100	965-228		963-128		
RXB 30K10M	30	10	10	200	965-228		963-128		
with elevated display									
RXB 3K1HM	3	1	1	20	965-227		963-127		
RXB 6K2HM	6	2	2	40	965-228		963-128		
RXB 15K5HM	15	5	5	100	965-228		963-128		
RXB 30K10HM	30	10	10	200	965-228		963-128		

Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.

KERN Pictograms

 Internal adjusting (CAL): Quick setting of the balance's accuracy with internal adjusting weight (motordriven).	 Adjusting program (CAL): For quick setting of the balance's accuracy. External adjusting weight required.	 Memory: Balance contains memories, e.g. for item data, weighing data, tare weights etc. PLU
 Data interface RS-232: To connect the balance to a printer, PC or network	 Control outputs (optocoupler, digital I/O) to connect relays, signal lamps, valves, etc.	 Interface for second balance: for direct connection of a second balance
 Network interface: For connecting the scale to an Ethernet network. With KERN products you can also use a universal RS-232/LAN converter.	 GLP/ISO record keeping: of weighing data with date, time and identification-no. Only with printers from KERN.	 Piece counting: Reference quantities selectable. Display can be switched from piece to weight
 Net-total weighing: weight of tare cup and weight of components memorized in two separate stores.	 Percentage determination: Determining the deviation in % from the target value (100%).	 Weighing units: Can be switched to e. g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.
 Weighing with tolerance range: Upper and lower limiting can be programmed individually, e.g. dosing/sorting and portioning.	 Vibration-free weighing: (Animal weighing program) Vibrations are filtered out so that a stable weight is obtained.	 Spray and dust protection IPxx: The type of protection is shown by the pictogram. For details see the glossary.
 Stainless steel: the balance is protected against corrosion.	 Suspended weighing: load support with hook on the underside of the balance.	 Battery operation: Ready for battery operation. The battery type is specified for each device.
 Rechargeable battery pack: rechargeable set.	 Mains adapter: 230V/50Hz in standard version for Germany. On request GB, AUS or USA version.	 Power supply: integrated in balance. 230V/50Hz in Germany. More standards e. g. GB, AUS, USA on request.
 Strain gauges: Electrical resistor on an elastic deforming body.	 Tuning fork principle: A resonating body is electromagnetically excited, causing it to oscillate.	 Electromagnetic force compensation: Coil in a permanent magnet. For the most accurate weighings.
 Single cell technology: Advanced version of the force compensation principle with the highest level of precision.	 Verification possible: The time required for verification is specified in the pictogram.	 DKD calibration possible: The time required for DKD calibration is shown in days in the pictogram.
 Package shipment: The time required to manufacture the product internally is shown in days in the pictogram.	 Pallet shipment: The time required to manufacture the product internally is shown in days in the pictogram.	 Warranty: The warranty period is shown in the pictogram.

Precision is our business

To ensure the high level of precision of your balance, KERN offers the appropriate test weight package for your balance. This consists of the test weight, box and DKD calibration certificate, as proof of its accuracy. The best way to ensure proper balance calibration.

In the extensive KERN test weight range, you will find test weights in the international OIML error limit classes: E 1, E 2, F 1, F 2, M 1, M 2, and M 3 with weights from 1 mg to 2000 kg.

The KERN DKD calibration laboratory for electronic balances and weights has been accredited by DKD since 1994 and today is one of the most modern and best-equipped DKD calibration laboratories for balances, test weights and force-measurement in Europe. (DKD = German Calibration Service ~ UKAS)

Your KERN specialist dealer:


Thanks to the high level of automation, we can carry out DKD calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DKD calibration of balances with a maximum load of up to 6000 kg
- DKD calibration of weights in the range of 1 mg – 500 kg
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DKD calibration certificates in the following languages
D, GB, F, I, E, NL, PL

Do you have questions about your scale, the corresponding test weight or the calibration service? Your KERN specialist dealer will be pleased to assist you.

KERN – Professional measuring. Measuring technology and testing services from a single source



German Excellence Group
Member