

VKT-Tuotanto

Nyåkerintie 37, 02420 Jorvas

puh. 09-2970201, myyntipäivystäjä 0500-738122

myynti@vkt-tuotanto.fi

www.vkt-tuotanto.fi



MCWN "NINJA" SERIES SUSPENDED CRANE SCALES



Easy to use and reliable professional digital crane scales, for weighing in industrial environments, fitted with protective transport case. Thanks to their compact size, the MCWN crane scales reduce just slightly the lifting distance of the crane. Available also CE-M APPROVED. Fitted with test certificate obtained with sample weights.

MAIN FEATURES

- Fitted with the following upper and lower shackle:
GR3 for MCWNT1
GR6 for MCWNT6
GR9 for MCWNT9.
- Compact size and minimum distance between upper and lower shackle.
- 25 mm LCD backlit display, easily visible in any lighting condition.
- Precision: +/- 0.03% on MAX.
- 5-key waterproof keypad: Zero, semi automatic or preset Tare, Mode, Print, On/Off.
- Sturdy case in oven-fire painted steel.

NOTE: All versions are supplied with a certificate of calibration (made with sample weights of the full capacity range).

WEIGHTS OF THE CRANE SCALES

Models	Weight in kg	
	without packaging	including packaging
MCWNT1	6 kg	10 kg
MCWN11T6	10 kg	15 kg
MCWNT9	15 kg	19 kg



Protective transport case

- Fitted with infrared remote control for up to 8m distance use. The remote control can be configured by the customer as a single automatic tare or as a remote keypad.
- Power supply through 4 AA batteries, which may be rechargeable (operating time of about 40 hours).
- Digital calibration and programmable Set-Up directly from the keypad or from the PC with Dinitools.
- Programmable digital filter and auto switch-off.
- Operating temperature: -10 /+40 °C.
- RS232 serial port on the RJ45 connector for quick programming with Dinitools.
- Fitted with protective transport case with dimensions (WxLxH) 175x480x390mm.

MAIN FUNCTIONS

- Weighs accumulation.
- +/- check.
- Weigh percentile.
- Input/Output.
- Hold, for freezing the weight on the display.
- Peak, for identifying the weight peaks.
- X 10 high resolution visualisation.
- Net/Gross or lb/kg conversion.

Lataukset Dini Argeon sivuilta

- [CE_CERTIFICATE_SCALES_150318.pdf](#)
- [DFW_03.18_15.07_EN_T.pdf](#)
- [DiniTools_4.19.00.zip](#)
- [MCWN_03_15.10_DE_U.pdf](#)
- [MCWN_03_15.10_EN_U.pdf](#)
- [MCWN_03_15.10_FR_U.pdf](#)
- [MCWN_03_15.10_IT_U.pdf](#)
- [Printout examples_DFW.pdf](#)
- [Setup_WeiMonitor_1.5.7.zip](#)
- [TECHNICAL_DRAWING_MCWN-2_R2.pdf](#)
- [Last Firmware Revision News](#)

Mallisto

Code	Max (kg)	d (kg)	M (kg)
MCWNT1-2	300/600/1500	0,1/0,2/0,5	--
MCWNT1M-2 M	1500	--	0,5
MCWN11T6-1	1500/3000/6000	0,5/1/2	--
MCWN11T6M-1 M	6000	--	2
MCWNT9-1	3000/6000/9500	1/2/5	--
MCWNT9M-1 M	9000	--	5



CT6 ISO 17025 calibration certificate from 301 to 1500 kg. For precision and industrial scales, crane scales.



CT7 ISO 17025 calibration certificate from 1501 to 3000 kg. For precision and industrial scales, crane scales.



CT8 ISO 17025 calibration certificate from 3001 to 15000 kg. For crane scales.

Lisätarvikkeet



Code	Description
GG1T5	Swivelling bottom hook with safety lock 1,5 t.
GG7	Swivelling bottom hook with safety lock 7 t.
GG15	Swivelling bottom hook with safety lock 15 t.
CA2	Connection ring 2 t.



CA8 Connection ring 8 t.



CA15 Connection ring 15 t.

Other options

Code	Description
TECSUP	Technical assistance by telephone. NET Hourly price.
UMAN	Printed user manual. (Free if downloaded from the web). €NET.
TECMAN	Printed technical manual. (Free, if downloaded from the web). €NET.