

VKT-Tuotanto

Nyåkerintie 37, 02420 Jorvas

p. 09-2970201, 0500-738122

myynti@vkt-tuotanto.fi myyntipäivystäjä www.vkt-tuotanto.fi



"WALL-E INOX" SERIES STAINLESS STEEL BENCH AND FLOOR SCALES



Bench and floor scales with column, characterized by multifunction weight indicator, completely stainless steel structure. Easy to use and versatile, guaranteeing precision and reliability. Particularly suitable for industrial and commercial use. Available also in CE-M approved version according to OIML R-76 / EN 45501 standards.

TECHNICAL FEATURES

- **Weight indicator with waterproof IP65 STAINLESS STEEL case. Backlit 25mm LCD display with 6 high contrast digits and icons for indication of active functions. Waterproof 5-key functional keypad.**
- **Functions with an aluminium load cell, protected in IP65 stainless steel cover, approved according to OIML R60 C3 standards (3000 divisions).**
- **Stainless steel structure, with adjustable resting feet and level.**
- **Stainless steel loading surface, size: see the table.**
- **Support column, height:**
 - 350 mm in the "T" models;
 - 500 mm in the "Q" models;
 - 700 mm in the "X" models.

I/O SECTION

- RS232/RS485 port for connection to PC, PLC or repeater.
- RS232 port configurable for connection to printer.

- IR input for managing the remote control.
- **Digital calibration and set-up from keypad or from PC with DINITOOLS.**
- **Power supply: 230 Vac power supplier.**

SELECTABLE FUNCTIONS

- **X 10 high resolution visualisation**
- **Net/Gross or lb/kg conversion**
- **Weighs totalisation**
- **Formulation**
- **Counting**
- **+/- Check**
- **Percentage weighing**
- **Alibi (with optional interface)**
- **HOLD (freezing the weight on the display)**

KEYBOARD AND PRINTING FUNCTIONS

- **KEYBOARD: Zeroing, Automatic tare, Presetable tare, printing and/or data transmission, selectable function command, on/off switching.**
- **PRINTING: Configurable print layout with:**
 - **4 heading lines**
 - **Gross-Tare-Net and ticket number**
 - **Date and time (only with DFCLK)**
 - **Print of barcode 39.**

Code	l x w x h (mm)	Max (kg)	d (g)	M (g)*
WETI6-1	300x300x130	6	2	2
WETI15-1	300x300x130	15	5	5
WETI30-1	300x300x130	30	10	10
WEQI30-1	400x400x140	30	10	10
WEQI60-1	400x400x140	60	20	20
WEQI150-1	400x400x140	150	50	50
WEXI60-1	600x600x150	60	20	20
WEXI150-1	600x600x150	150	50	50
WEXI300-1	600x600x150	300	100	100

(*) These divisions are obtainable only with the relative options

Calibration service (ACCREDIA/DAKKS) only at time of order

Code Description



CT4 ISO 17025 calibration certificate from 6 to 60 kg. For precision and industrial scales, crane scales.



CT5 ISO 17025 calibration certificate from 61 to 300 kg. For precision and industrial scales, crane scales.

Legal for trade approval



Code	Description
ECEM	CE-M Single platform legal for trade approval.

Storing the weighs (only at time of order)

Code Description



SWM WeiMonitor PC program for monitoring and recording weighs in real time, from one or more scales.

Connection cables

Code	Description
RSCBUSB-1	USB PC/RS232 converter cable, l=1,5m. USB/RJ11 connector.



Columns, supports brackets, visors

Code	Description
PBISTF	Stainless steel fixing bracket for mounting the DFWLI indicator.

